



Case Study: Residential

Sprecher Residence

Industry: Residence
Location: Marin, California
Architect: Hershon Hartley Design

Bamboo Everywhere

In this residence, Amber Edge Grain plywood was utilized for the ceilings, custom designed single stringer stair treads with beveled edges and all the flooring.

The uniformity of ceiling, wall and floor brings warmth and consistency regardless of where the eye wanders. The consistent materials set off the other.



Materials Used:




Amber Edge Grain
Bamboo Plywood
BP-V019A-NAUF/FSC



Specifications

Possible LEED Credits:

Low emitting materials and certified wood



Physical / Mechanical Properties - Edge Grain Bamboo Plywood

Dimensions:	3/4" x 48" x 96" 19mm x 1219mm x 2438mm (*mm tolerance +/- .5mm thickness)
Construction:	Three-ply, cross core construction.
Working with Plyboo:	A worksheet is provided with each panel containing useful tips and information and is also available on our website at plyboo.com/downloads .
ASTM E84: Surface Burning	Class C
ASTM D1037: Dimensional Stability	<ul style="list-style-type: none"> • Linear Expansion (3-ply): Parallel -0.04% / Perpendicular -0.07% • Thickness Swell (3-ply): -0.13% Screw Hold (3-ply) (face/back/edge) <ul style="list-style-type: none"> • 742 lbs/ 831 lbs/ 860 lbs average
ASTM D4442: Moisture Content	6-9% average
ASTM D 6007-02: Formaldehyde Concentration in Air from Wood Products, small chamber test	Plyboo = 0.004 ppm (surpasses CARB II standards, 0.05ppm & ULEF standards of 0.04ppm)